



TSP654SK

Liner-Free Printer



The TSP654SK Liner-Free printer is designed to work with liner-free labeling applications. Repositionable thermal labels can stick to virtually any surface, and can be removed easily and reapplied leaving behind no residue. The liner-free labels are an alternative to using silicone-lined labels or tape.

Since it uses no silicone liner it eliminates the negative environmental impact and helps cut back on in-house waste, thus continuing Star Micronics Global Green Initiative, which encompasses manufacturing products that provide the minimalist impact possible on our environment.

Liner-free labels are a welcomed addition for quick service restaurants (QSR) applications, from drive-through service self-service deli applications. The liner-free labels can be used for an exception sandwich only or the entire order by attaching it to the bag. The labels can stay with and track an order through the entire preparation process, improving both drive-through, and take-out order accuracy, and a better bottom line.

Visit www.starmicronics.com to learn more.

- Repositionable, Liner-Free Thermal Label Solution
- Improves Order Accuracy Up to 99%
- Environmentally Friendly
- Liner Free Yields 60% More Labels/Roll than Diecut
- 80mm and 58mm Label Support
- High Reliability and Performance at a Low Cost
- "Drop-In & Print" Paper Loading
- Optional Vertical Stand




Library



Tote



Deli



Will Call



TSP654SK Specifications

		The Complete Legacy POS Solution!	
Features	<p>Hardware "Drop-In & Print" Clamshell Design Reliable Guillotine Cutter Small Footprint Swappable Communication Interface Horizontal & Vertical Use Recessed Cable Connections</p>	<p>Software (Included in Windows® Drivers) Logo Utility (Store Logos, Coupons, and Graphics) Memory Switch Utility Ethernet Interface Setup Utility Virtual Serial Port for Legacy Applications</p> <p>StarIO SDK Available</p>	
Connectivity	<p>Note: Connections in bold are supported; grayed-out connection types may be supported by special request.</p> <p>9-Pin Serial 25-Pin Serial Parallel USB Powered USB Ethernet Wireless LAN Dual 9-Pin Serial/USB</p>	<p>Virtual Serial Port to USB Virtual Serial Port to Ethernet Virtual TCP/IP Port</p>	
Drivers	<p>Windows® XP Vista (32 bit / 64 bit) Windows 7 (32 bit / 64 bit) Server 2008 (32 bit / 64 bit) CE XP Embedded POS for .NET</p>	<p>OPOS™ JavaPOS™ USB Vendor Class Linux™ CUPS Mac OS X CUPS</p>	
What's Included	<p>Printer Installation CD (Printer Driver / Manuals) Setup Sheets Wall Mount Bracket 58mm Paper Guide Power Switch Cover Start up Liner-Free Label Roll</p>		
Optional Accessories	<p>External Power Supply (PS60A) Putty or Gray Color Housing Splash Proof Cover (SPC-T100) Integrated Buzzer (BU01-24-A) Vertical Stand (VS-T650)</p>		
Technical Specifications	<p>Print Method : Direct Thermal Print Speed : 150mm/s (30 Receipts Per Minute) Paper Width : 80mm / 58mm Paper Thickness : 0.0031 – 0.0034in Paper Diameter : Max 83mm Emulation : Star Line Mode, ESC/POS™</p>	<p>Power : DC24V Resolution: 203 dpi Dimensions: W=142mm, H=132mm, D=202mm</p>	
Warranty	<p>For US and Canada: 3-Year Limited Warranty, Plus Optional Extended Services Agreement Policies (Extend-A-Star and Swap-A-Star)</p>		
For Further Information	<p>Sales: 1-800-782-7636 x107 Technical Support: 1-800-782-7636 x105</p>	<p>Web: http://www.starmicronics.com</p>	

11/11/13

