



CS60 series Technical Accessory Guide



NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.




This document and the information contained therein (Information) are Zebra- confidential, and are provided under, and subject to, the confidentiality provision of your PartnerConnect agreement with Zebra. Any public disclosure (via posting on your website or otherwise) of the Information is strictly prohibited and will be considered a violation of your PartnerConnect agreement with Zebra.

** Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.*

Cradles/Charging



Part Number	Description	Notes	Required Items
CR6080-SC100F4WW CR6080-SC100F4CN (for China only)	<p>Single Slot Device + Spare Battery Charge/Communication Cradle</p>	<ul style="list-style-type: none"> ▶ Cradle will charge CS60 and provide communications. ▶ Also charges one spare battery. ▶ Uses inductive charging for CS60 unit. ▶ Device communicates to cradle via Bluetooth. ▶ Cradle includes pager button to locate CS60 unit if lost. ▶ Cradle also includes beeper which can be enabled to sound for Virtual Tether events. ▶ Includes cap to cover spare battery charging slot if spare battery charging is not needed. 	<ul style="list-style-type: none"> ▶ USB-C to USB-A cable (CBL-CS6-S07-04) To power cradle without PC connection: <ul style="list-style-type: none"> ▶ USB Power Supply (PWR-WUA5V6W0WWW)

<p>CR6080-SC400F4WW</p>		<p>4-Slot Charge-Only Cradle KIT</p>	<ul style="list-style-type: none"> ▶ Cradle charges four CS60 units simultaneously. ▶ Does not charge spare batteries. ▶ Uses inductive charging. ▶ Uses Zebra ShareCradle design ▶ Kit includes: <ul style="list-style-type: none"> - 4-Slot Charge-Only Cradle Adapter Cup + ShareCradle base (CR6080-SC400F4WWNS) - Power Supply (PWR-BGA12V50W0WW) - DC Line Cord (CBL-DC-388A1-01) 	<p>AC Line Cord (23844-00-00R or country specific cord)</p>
<p>CR6080-SA40004WW</p>		<p>4-Slot Charge-Only Cradle Adapter Cup</p>	<ul style="list-style-type: none"> ▶ Cradle charges four CS60 units simultaneously. ▶ Does not charge spare batteries. ▶ Uses inductive charging. ▶ Allows existing Single or Multi-Slot ShareCradle to be modified to support CS60. Existing cradle cup can be removed from a ShareCradle and replaced with this CS60 cup. 	<p>▶ Existing Single or Multi-Slot ShareCradle (typically from a mobile computing product)</p>
<p>various (3rd party) *</p>		<p>Qi Charging Pad</p>	<ul style="list-style-type: none"> ▶ Allows CS60 unit to be charged. ▶ Just place the scanner on top of the pad 	




<p>CR6080-BC40004WW</p>		<p>4-Slot Spare Battery Charger KIT</p>	<ul style="list-style-type: none"> ▶ Cradle charges four CS60 batteries simultaneously. ▶ Uses Zebra ShareCradle design ▶ Kit includes: <ul style="list-style-type: none"> - 4-Slot Spare Battery Cradle Adapter Cup + ShareCradle base (CR6080-BC40004WWNS) - Power Supply (PWR-BGA12V50W0WW) - DC Line Cord (CBL-DC-388A1-01) 	<p>AC Line Cord (23844-00-00R or country specific cord)</p>
<p>CR6080-BA40004WW</p>		<p>4-Slot Spare Battery Charger Cup</p>	<ul style="list-style-type: none"> ▶ Cradle charges four CS60 batteries simultaneously. ▶ Allows existing Single or Multi-Slot ShareCradle to be modified to support CS60. Existing cradle cup can be removed from a ShareCradle and replaced with this CS60 cup. 	<p>▶ Existing Single or Multi-Slot ShareCradle (typically from a mobile computing product)</p>
<p>CR6080-PC100FBWW CR6080-PC100FBCN (for China only)</p>		<p>Healthcare Cart Mountable Device Communication Presentation Charge Cradle</p>	<ul style="list-style-type: none"> ▶ Cradle allows CS60 Healthcare models to operate in presentation mode. ▶ Can be mounted on cart or other fixture. ▶ Cradle will charge CS60 and provide communications. ▶ Uses inductive charging. ▶ Cradle includes pager button to locate CS60 unit if lost. ▶ Cradle also includes beeper which can be enabled to sound for Virtual Tether events. ▶ Device communicates to cradle via NFC when placed in cradle. Device communicates to cradle via Bluetooth when out of cradle. ▶ Uses same disinfectant ready plastics as CS60-HC models. ▶ Rear of cradle has two mounting holes for attaching to various brackets/mounting solutions. Holes use M4x5 screws (not included) and are spaced 45mm apart. 	<p>▶ USB-C to USB-A Cable (CBL-CS6-S07-0B)</p>




BRKT-SCRD-SMRK-01		5-Slot ShareCradle Mounting Bracket	<ul style="list-style-type: none"> ▶ Allows for rack and wall mounting of up to four 4-Slot Charge-Only Cradles or up to four 4-Slot Battery Chargers. ▶ Bracket can be mounted on standard 19" network rack or on a wall. ▶ Has cable routing slots and removable power supply tray that stores and conceals power supplies. ▶ Adjustable tabs & screw mounts for easy hanging/installation. ▶ Adjustable orientations: <ul style="list-style-type: none"> - 25° High Density (5-Slot Charge Only Cradle) - Horizontal (Single Slot Cradle or 4-Slot Battery Chargers). ▶ See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	
-------------------	---	-------------------------------------	---	--

Misc

Part Number	Picture	Description	Notes	Required Items
STND-GS0060C-04		Gooseneck Stand - Standard Base (SR Black color)	▶ Scanner enters into presentation mode when inserted into cup.	
STND-GS0060C-0B		Gooseneck Stand - Standard Base (Healthcare White color)	▶ Scanner enters into presentation mode when inserted into cup.	



STND-WS0060C-04		Gooseneck Stand - Weighted Base (SR Black color)	<ul style="list-style-type: none"> ▶ Scanner enters into presentation mode when inserted into cup. ▶ Stand features a weighted base to prevent tip-over. 	
STND-WS0060C-0B		Gooseneck Stand - Weighted Base (Heathcare White color)	<ul style="list-style-type: none"> ▶ Scanner enters into presentation mode when inserted into cup. ▶ Stand features a weighted base to prevent tip-over. 	
CUP-GS0060C-04		Stand Cup (SR Black color)	<ul style="list-style-type: none"> ▶ Scanner enters into presentation mode when inserted into cup. ▶ Cup can be attached to all Zebra Intellistand Bases or can be attached to custom designed mount. 	
CUP-GS0060C-0B		Stand Cup (Heathcare White color)	<ul style="list-style-type: none"> ▶ Scanner enters into presentation mode when inserted into cup. ▶ Cup can be attached to all Zebra Intellistand Bases or can be attached to custom designed mount. 	


LNYD-000060W-04		Neck Cord Lanyard	<ul style="list-style-type: none"> ▶ Allows CS60 to be worn around neck. ▶ Includes Silicon Case, Neck Cord and Retractor (SG-EC30-RET1-01) which is shared with the EC30. ▶ Case protects CS60 and provides accessory attachment point for the neck lanyard. ▶ Case must be removed to insert CS60 into Chargers or Cradles. ▶ Case has large cutout on top to ease removable of scanner for battery charging or insertion into cradle. 	
SG-EC30-RET1-01		Spare/Replacement Magnetic Retractor	Replacement retractor used with Neck Cord Lanyard (LNYD-000060W-04)	
Communication Cables				
Part Number	Picture	Description	Notes	Required Items
CVTR-U70060C-04		USB Converter Cable - Black	<ul style="list-style-type: none"> ▶ Cable converts CS60 to a corded scanner. Replaces battery. ▶ 7 ft. length, straight cable ▶ USB-A connector 	

CVTR-U70060C-0B		USB Converter Cable - White	<ul style="list-style-type: none"> ▶ Cable converts CS60 to a corded scanner. Replaces battery. ▶ 7 ft. length, straight cable ▶ USB-A connector 	
CBL-CS6-S07-04		USB-C to USB-A Cable for Cradles, Black color	<ul style="list-style-type: none"> ▶ Cable connects Single Slot Device + Battery Charge/Communication Cradle (CR6080-SC100F4WW or CR6080-SC100F4CN) to host. ▶ 7 ft. length, straight cable ▶ USB-A to USB-C connector 	
CBL-CS6-S07-0B		USB-C to USB-A Cable for Cradles, White color	<ul style="list-style-type: none"> ▶ Cable connects Healthcare Cart Mountable Device Communication Presentation Charge Cradle (CR6080-PC100FBWW or CR6080-PC100FBCN) to host. ▶ 7 ft. length, straight cable ▶ USB-A to USB-C connector 	









Bluetooth Adapters

The following Bluetooth adapters have been tested for compatibility with the CS6080

Part Number	Picture	Description	Notes	Required Items
Techkey-001 (3rd party) *		Techkey USB Mini Bluetooth 5.0 EDR Dongle	<ul style="list-style-type: none"> ▶ Bluetooth 5.0+EDR adapter, Bluetooth low energy. ▶ Fast and further working distance than Bluetooth 4.0 Supports Bluetooth speakers, headphones, headsets, keyboards, mice, and more. Can work with 7 devices at the same time. Can work with Bluetooth printer and stereo headphone maximum transfer rate up to 3Mbps and transmission distance up to 33ft/10M in open space. ▶ Extremely compact USB adapter allows you to leave it on laptop or PC, no need to remove, without blocking surrounding USB ports, save space ▶ Bluetooth 5.0+ EDR, it is backward compatible with Bluetooth 2.0/2.1/3.0/4.0/4.2 Dual-mode Bluetooth transfer, compatible Full-speed USB 2.0 interface, USB 1.1 ▶ Supports Win7/Win8/Win8.1/Win10 (needs driver) 	
USBBT2EDR4 (3rd party) *		Startech Mini USB Bluetooth 4.0 Adapter	<ul style="list-style-type: none"> ▶ Bluetooth® 4.0 LE +EDR compliant Bluetooth Smart Ready transceiver ▶ Class 2 device with 10m (33ft) effective range ▶ Support for Enhanced Data Rate (EDR) with data transfer rates up to 3 Mbps 	

<p>GBU521 (3rd party) *</p> <p>www.iogear.com</p>		<p>IOGear Micro USB Bluetooth 4.0 Adapter</p>	<ul style="list-style-type: none"> ▶ Bluetooth® 4.0 LE +EDR compliant Bluetooth Smart Ready transceiver ▶ Class 2 device with 10m (33ft) effective range ▶ Support for Enhanced Data Rate (EDR) with data transfer rates up to 3 Mbps 	
---	---	---	--	--

Power Cords

Part Number	Picture	Description	Notes	Required Items
PWR-WUA5V6W0WW		USB Power Supply	<ul style="list-style-type: none"> ▶ Used to charge CS60 in Single Slot Charge/Communication Cradle (CR6080-SC100F4WW) without a PC. ▶ Includes four international plugs for use in US, UK, EU, and AU. Additional plugs can be purchased separately for other countries. ▶ 5.2V, 1.2A, 6W output ▶ Provides US DOE Level VI compliance for power efficiency 	
PWR-WUA5V6W0WHT		USB Power Supply, White color	<ul style="list-style-type: none"> ▶ Used to charge CS60 in Single Slot Charge/Communication Cradle (CR6080-SC100F4WW) without a PC. ▶ Includes four international plugs for use in US, UK, EU, and AU. Additional plugs can be purchased separately for other countries. ▶ 5.2V, 1.2A, 6W output ▶ Provides US DOE Level VI compliance for power efficiency 	
CN-000803-01		<u>Spare/Replacement</u> USB Power Supply AC Clip for Australia (AUS)	<ul style="list-style-type: none"> ▶ This AC Clip is normally included with PWR-WUA5V6W0WW ▶ 2 pin Australia plug 	USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-02		USB Power Supply AC Clip for Argentina (ARG)		USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-03		USB Power Supply AC Clip for Korea (KOR)		USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-04		<u>Spare/Replacement</u> USB Power Supply AC Clip for US (US)	<ul style="list-style-type: none"> ▶ This AC Clip is normally included with PWR-WUA5V6W0WW ▶ 2 pin US plug 	USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-05		<u>Spare/Replacement</u> USB Power Supply AC Clip for Europe (EU)	<ul style="list-style-type: none"> ▶ This AC Clip is normally included with PWR-WUA5V6W0WW 	USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-06		<u>Spare/Replacement</u> USB Power Supply AC Clip for UK (UK)	<ul style="list-style-type: none"> ▶ This AC Clip is normally included with PWR-WUA5V6W0WW 	USB Power Supply (PWR-WUA5V6W0WW)

CN-000803-07		USB Power Supply AC Clip for China (CHN)	▶ straight pins China plug	USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-08		USB Power Supply AC Clip for Brazil (BRA)	▶ 2 pin Brazil plug	USB Power Supply (PWR-WUA5V6W0WW)
CN-000803-09		USB Power Supply AC Clip for India (IND)		USB Power Supply (PWR-WUA5V6W0WW)
PWRS-124306-01R		USB Power Supply	<ul style="list-style-type: none"> ▶ Used to charge CS60 in Single Slot Charge/Communication Cradle (CR6080-SC100F4WW) without a PC. ▶ Includes four international plugs for US, UK, EU, and AU ▶ 5V, 1.2A output ▶ Discontinued 3/2017, now use PWR-WUA5V6W0WW 	
CBL-DC-388A1-01		DC Power Cord	<ul style="list-style-type: none"> ▶ Used to power 4-Slot Charge-Only Cradle and 4-Slot Battery Chargers when using Level VI Efficiency power supply (PWR-BGA12V50W0WW) ▶ Cable length is 1.8 meters ▶ NOTE: 4-Slot Charge-Only Cradle includes this cable. 	
PWR-BGA12V50W0WW		Power Supply	<ul style="list-style-type: none"> ▶ Used to power 4-Slot Charge-Only Cradle and 4-Slot Battery Chargers. ▶ 100-240 VAC, 12V, 4.16A, 50W ▶ Provides US DOE Level VI compliance for power efficiency. ▶ Replaces PWRS-14000-148R ▶ NOTE: 4-Slot Charge-Only Cradle includes this power supply. 	DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R)
PWRS-14000-148R		Power Supply with integrated DC Cord	<ul style="list-style-type: none"> ▶ Discontinued 1/2017, now use PWR-BGA12V50W0WW and CBL-DC-388A1-01 - see PMB 2903. ▶ Replaces KT-14000-148R ▶ Used to power 4-Slot cradle chargers ▶ 100-240 VAC, 12VDC, 3.33A ▶ Energy Star Compliant 	23844-00-00R
50-14000-148R		Power Supply with integrated DC Cord	<ul style="list-style-type: none"> ▶ Discontinued 12/2007 - replaced by KT-14000-148R ▶ Used to power 4-Slot cradle chargers 	23844-00-00R
KT-14000-148R		Power Supply with integrated DC Cord	<ul style="list-style-type: none"> ▶ Replaces 50-14000-148R ▶ Used to power 4-Slot cradle chargers ▶ Discontinued 12/2010 - now use PWRS-14000-148R 	23844-00-00R
23844-00-00R		AC Line Cord	Used with AC Power Supply (PWR-BGA12V50W0WW)	

Batteries

Part Number	Picture	Description	Notes	Required Items
-------------	---------	-------------	-------	----------------

<p>BTRY-CS60EAB0E-04</p> <p>BTRY-CS60EAB0E-04K (for use in India, Korea & Japan)</p>		<p>CS60-SR Spare Battery (Black)</p>	<p>► For non-Healthcare version ► 735 mAh Lithium ion</p>	
<p>BTRY-CS60EABHE-0B</p> <p>BTRY-CS60EABHE-0BK (for use in India, Korea & Japan)</p>		<p>CS60-HC Spare Battery (White)</p>	<p>► For Healthcare version ► 735 mAh Lithium ion</p>	